

## **S24015P12NF**Directional Panel Antenna

Innovative **Technology** for a **Connected** World




## **HIGH GAIN 2.4 - 2.5 GHz DIRECTIONAL ANTENNA**

The S24015P12NF antenna offers the user a high-gain alternative to a yagi antenna in a much smaller package. The antenna is enclosed in a weather resistant UV stable housing that can be either mast or wall mounted using its articulating mount. E and H plane beamwidths (30°) are conducive to point-to-point bridge applications and the antenna's panel form factor allows it to be mounted inconspicuously.

## **MARKETS**

WiMAX

MODEL	SPECIFICATION
Frequency (MHz)	2400 -2500
Gain (dBi)	15
E-Plane (3 dB beamwidth)	29°
H-Plane (3 dB beamwidth)	31°
Polarization	Linear
Weight lb. (kg)	1.5 (.57)
VSWR	1.5:1
Mounting style	Mast / ceiling
Dimensions in (cm)	10 x 10 x 1.5 (25.4 x 25.4 x 3.8)
Front to back ratio	24 dB
Power (watts)	50
RF connector (f)	N



global solutions: local support ™

ANT-DS-S24015P12NF 0611

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies materials or products for any specific or general uses. Laird Echnologies in the tellable for into the liable for into the liabl