



The Laird vehicular 3-port MIMO antenna covers the 698-960/1710-2700 MHz, as well as GPS (1575.42 MHz) frequency ranges. Configured with 2-port, dual-band elements in addition to 1-port with integrated GPS.

Connector options include SMA male connectors for 3G/4G LTE and GPS ports with an RSMA male connector for the Wi-Fi port. The housing incorporates a low profile, rugged design that meets IP67 standards. The antenna also features high impact, UV-resistant polycarbonate plastic available in black or white.

ELECTRICAL SPECIFICATIONS		
Number of Ports	3 (2-ports – 3G/4G LTE; 1-port – GPS)	
Operating Frequency (MHz)	698-960 MHz	1710-2700 MHz
Peak Gain (dBi)*	2.6	4.7
Isolation Port 1 – 2 (dB)*	>15	>20
VSWR – Avg*	<1.8:1	
VSWR – Max*	<2.0:1	
Nominal Impedance (Ohms)	50	
Max Power - Ambient 25°C (W)	50	
Polarization	Vertical Linear	
Azimuth Beamwidth	Omnidirectional	

* Measured on 304.8 mm (1 ft.) diameter ground plane

MECHANICAL SPECIFICATIONS	
Dimensions – mm (in.)	132 x 75 (5.2 x 2.9)
Weight – kg (lb.)	0.74 (1.63)
RF Connector	SMA-Male (3G/4G ports)
Cable (exposed length) – cm (ft.)	LMR195M- 518.2 (17)
Radome/Baseplate Material	PC, UL94 - V0 Rating, UV Stable (Black and White)

ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature – °C (°F)	-30 to +70 (-22 to +158)
Ingress Protection Rating	IP67
Material Substance Compliance	RoHS

PART NUMBER	DESCRIPTION
VLT69273B2NG-518A	2-Ports 4G/LTE, 1-Port GPS: SMA Male (Black)
VLT69273W2NG-518A	2-Ports 4G/LTE, 1-Port GPS: SMA Male (White)

GPS ANTENNA SPECIFICATIONS			
Frequency Band (MHz)	1575.42 (GPS L1)		
Bandwidth (MHz)	6 (Typical)		
Amplifier Gain (dB)	27 (± 3 dBc)		
Nominal Impedance (Ohms)	50		
Output VSWR	<1.5:1		
DC Voltage	2.7 – 12 Vdc		
DC Current	20 mA (Nominal); 30 mA (-40°C - +85°C)		
Out-of-Band Signal Rejection	> 40 dB rejection @ ± 50 MHz from center frequency		
Intermodulation @ CW Mode (-40° C to +85° C)	Int1	Int2	IM3
Power, dBm	-10 (1842.8 MHz)	-10 (2110 MHz)	-100 (1575.6 MHz)
Power, dBm	-10 (829.58 MHz)	-10 (2405 MHz)	-100 (1575.42 MHz)
Power, dBm	-10 (755.42 MHz)	-10 (820 MHz)	-100 (1575.42 MHz)
Input 1 dB Compression @ 750 MHz, 2000 MHz, 3500 MHz	> 10 dBm (-40°C - +85°C)		
Connector	SMA-Male		
Cable – Exposed Length	RG174-518.2 cm (17 ft.)		

Americas: +1.847.839.6925
 IAS-AmericasSales@lairdtech.com
Europe: +44.1628.858941
 IAS-EUSales@lairdtech.com
Asia: IAS-AsiaSales@lairdtech.com
Middle East and Africa:
 +44.1628.858941
 IAS-MEASales@lairdtech.com
<https://connectivity.lairdtech.com>



Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request.

© Copyright 2018 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

